



We create chemistry

## Product specification

### Texapon® N 70 T

PRD 30528351

Valid since 30.04.2019  
Revision 4.5  
WF-No. 19945  
Page 1 of 3

® = registered trademark of BASF in many countries    ™ = Trademark of BASF

**Care Chemicals**

### Characteristic values

The specifications stated in the paragraphs 'Quality control data' and 'Additional product descriptive data' finally and conclusively describe the properties of the product.

**INCI name:** Sodium Laureth Sulfate  
**Physical form:** Flowable paste

#### Quality control data

(Data which is used for quality release and is certified for each batch.)

Test property	Specification
Appearance at 25 °C	Transparent to yellowish, flowable paste
Odor at 25 °C	Corresponds to the standard
Active ingredient (MW 384)	69.0 - 72.0 %
pH value (25 °C; 3 % solution)	7.0 - 9.0
1,4-Dioxane	max. 30 ppm
Unulfated matter	max. 2.8 %
Sodium sulfate	max. 1.0 %
Color APHA (25 °C; 20 % aq. solution)	max. 25

Specific methods used for batch release see Certificate of Analysis. Only the data displayed in this document shall constitute the agreed contractual quality of the product. Chemical-physical characteristics reported in other product related documents (e.g. MSDS, Marketing brochures etc.) are not intended to define the quality of the product. Conversely, Product Specification does not address product communication, human and/or environmental safety or socio-economical characteristics.



We create chemistry

## Product specification

---

### **Texapon® N 70 T**

PRD 30528351

Valid since 30.04.2019  
Revision 4.5  
WF-No. 19945  
Page 2 of 3

---

® = registered trademark of BASF in many countries    ™ = Trademark of BASF

**Care Chemicals**

## Storage information

### **Shelf life**

12 months

### **Storage temperature**

Between + 20 °C and + 40 °C

### **Storage conditions**

In original sealed containers and protected from moisture

### **Additional information**

Texapon® N 70 T should be protected against frost as the product becomes solid, however by carefully raising the temperature the product can be returned to its original state. At temperatures below + 20 °C flowability decreases, below 10 °C pumping is not possible. To make handling easier and for bulk transport the temperature of Texapon® N 70 T can be raised to approximately 50 °C for a short period without impairing the product quality. However prolonged storage should be at the lowest temperature possible to avoid any potential impairment. To raise the temperature of Texapon® N 70 T a warm water system with a maximum temperature of 60 °C is recommended. Under no circumstances may steam or an electric heating system be used to raise the temperature of the product. This will cause local surface overheating and irreversible damage to the product and storage tank. Depending on the temperature, the pH value may decrease during storage and must be appropriately monitored by the customer. The product is not negatively influenced at a pH values above 4.0. Due to the high active content, the addition of a preservative is not necessary. As a consequence of storage or transportation, slight separations may occur which can be eliminated by stirring.



We create chemistry

Product specification

---

**Texapon® N 70 T**

PRD 30528351

Valid since 30.04.2019

Revision 4.5

WF-No. 19945

Page 3 of 3

---

® = registered trademark of BASF in many countries    ™ = Trademark of BASF

**Care Chemicals**

**Intended for use as cosmetic and home care ingredient**

The aforementioned data shall constitute the agreed contractual quality of the product at the time of passing of the risk. The data are controlled at regular intervals as part of our quality assurance program.

SELLER MAKES NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, BY FACT OR LAW, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This is a computer generated document. It is valid without signature.